



Multi-Diag[®] Pocket 2

Reference
AT 561 5000

- **Multi-Diag Pocket 2** is a compact device for complex electronic control units diagnostics
- **Multi-Diag Pocket 2** allows diagnostics of cars equipped OBD diagnostic connector
- For diagnostics of old cars can be used universal adapter (which is in set included) or adapters for individual car makes - see options **Multi-Diag Adapters**
- Software update is possible by CD or via Internet



Multi-Diag VCI 2 BT (Communic. interface)

- ISO 9141
- ISO 14230 (KWP 2000)
- ISO 11519-4
- ISO 15765 (CAN)
- SAE J2534 (Pass Thru device)
- GMW 3089 (GMLAN Single Wire CAN)



Fanless Technology
SSD 16GB (instead of the internal hard disk)



Multi-Diag Pocket 2

- Time to exit of standby mode is less than 5 seconds
- Test of fall – mechanical resistance
- Ergonomic design with emphasis on garage environment
- Touch screen allowing mouse functions
- Pocket 2 is one of the first industrial devices using Windows 7



µP	Intel ATOM 1.2 GHz
Memory	1GB
HDD	SSD 16GB
OS - Platform	Windows 7 Home Premium OEM
Screen	1024 x 600 (Widescreen)
Display	Color 7", Touch Screen
Working	5 h. (in use) / 6 h. (sleeping)
Express Diag time (average)	1min 55s
Dimension	22.1 x 11.7 x 2.25 cm
Weight	660g
WLAN	WiFi 802.11b/g
Bluetooth	2.0+EDR
Multimedia	Microphone, webcam



Set Multi-Diag Pocket contains

- Rubber cover on the tablet 7 "
- VCI 2 BT Communication interface
- BlueTooth
- External DVD reader through USB
- Communication cable EOBD
- Carrying bag